

# Buffalo LinkStation root access

<https://josephlo.wordpress.com/2011/04/16/setting-up-the-buffalo-linkstation-quad-pro-nas-part-2/>

On PC:

```
java -jar acp_commander.jar -t 192.168.1.207 -ip 192.168.1.207 -pw plange69
-c "ls /"
#java -jar acp_commander.jar -t 192.168.1.207 -ip 192.168.1.207 -pw plange69
-c "(echo ABCDEF;echo ABCDEF)|passwd"
#java -jar acp_commander.jar -t 192.168.1.207 -ip 192.168.1.207 -pw plange69
-c "sed -i 's/UsePAM yes/UsePAM no/g' /etc/sshd_config"
java -jar acp_commander.jar -t 192.168.1.207 -ip 192.168.1.207 -pw plange69
-c "sed -i 's/PermitRootLogin no/PermitRootLogin yes/g' /etc/sshd_config"
java -jar acp_commander.jar -t 192.168.1.207 -ip 192.168.1.207 -pw plange69
-c "/etc/init.d/sshd.sh restart"
```

On LinkStation:

```
wget https://bin.entware.net/armv5sf-k3.2/installer/generic.sh
sh generic.sh
opkg update
```

Package list: <https://bin.entware.net/armv5sf-k3.2/>

From:

<https://rpi64-wired.seanys.com/> - **It's in The Wiki**

Permanent link:

[https://rpi64-wired.seanys.com/buffalo\\_linkstation\\_root\\_access](https://rpi64-wired.seanys.com/buffalo_linkstation_root_access)

Last update: **2025/11/01 23:50**

